

ESAP 2020 SERIES BUS EMERGENCY EXIT HATCH









DESIGN

Complies to ADR44/02 Specification

SIZE

To suit Aperture length 810 (+2,-0)mm, width 618(+2,-0)mm. Accomodates 38mm to 70mm roof thickness & roof Camber radius of 7m.

MATERIAL

Dome: High impact ABS Plastic Frame: Aluminium Extrusion welded to AS1665 Seal: Black EPDM rubber double seal system

FINISH

Dome: White Inside and Outside Frame: White Powder coat to AS3715

INTERNAL TRIM

Black PVC Plastic: roof thickness 38mm to 56mm Black EPDM rubber: roof thickness 56mm to 70mm

VENTILATION OPERATION

Raise or Lower the dome by pushing or pulling the 'T' handles.

EMERGENCY OPERATION

Ensure the dome is in the raised position & operate the emergency lock catch as per illuminated instructions on dome. Dome swings fully open 95-100 degrees for ease of exit through the hatch in the emergency position.

LED ELECTRICAL SYSTEM

Encapsulated blue LED lighting IP rating- IP65 Life Span Hours: 35,000 hrs Moulded LED cover

ROOF THICKNESS	НАТСН ТҮРЕ	ESAP HATCH P/N
38-50mm	Emergency	ES14-6402VA1
56-70mm	Emergency	ES14-6402VA2
56-70mm	Emergency with Micro Switch	ES14-6402VA3
56-70mm	Non-Emergency	ES14-6402VA4

OLD LED KIT PN	NEW LED KIT PN	
SP31-095	-522 4500	
SP32-998	zES32-4506	

Version 4 - 30 January 2023